

# Handwashing & Sanitizing Stations

## specifications

### Classic Construction:

Classic cabinets (sides, back, sub-top, and sub-bottom) are constructed using fully doweled 0.75" particle board with double sided thermal fused laminate (TFL) with matching 3mm PVC edge banding\*. 1" matching, double sided high pressure laminate top (HPL) with matching 3mm PVC edge banding\* over sub-top.

Doors are 0.75" double sided TFL with matching 3mm PVC edge banding\*, 4" satin nickel wire pulls and 6-point adjustable concealed hinges (European hinge).

Integrated, 1" caster base with matching 3mm PVC edge banding\*, 3" heavy-duty casters (two locking and two non-locking), casters are installed onsite by others.


### Assembly:

Each unit is factory assembled using glue and dowel construction.

**Premium cabinets** are constructed the same as the Classic **EXCEPT** the Premium cabinet components are **double sided high pressure laminate (HPL)** in place of the double sided TFL.

\*3mm PVC edge banding is matching, unless otherwise specified. Complementary color available upon request.


### Standard Features:



.75" fully doweled casebody construction



1" HPL top



Wire pulls



6-point adjustable hinge



3" heavy-duty locking plate caster



3" heavy-duty plate caster

### The following are included on both the Handwashing Station and the Sanitizing Station:

- 10 gallon plastic trash bin
- Stainless steel hygiene station is constructed with 18-gauge stainless steel, type 300 with #4 polish satin finish. Station includes a wall mount soap & sanitizer dispenser and compartments to hold gloves, masks or tissue. (Gloves and masks are not included.)



### The following are included ONLY on the Handwashing Station:

- Stainless steel sink
- Choice of a hands free electronic sensor (CJ & HJ units) or water saving metering faucet (CM & HM units)
- Choice of cold water only or hot and cold water faucet (flow rate is 0.5GPM)
- 5 gallon removable fresh water tank (no disassembly required to refill)
- Hot water heater for HM & HJ units. Hot water unit is placed behind the 5 gal. fresh water tank.
- 7 gallon removable waste water tank includes a drain hose for easy draining (no disassembly required to drain)



V031122 Version subject to change



MCC4500

### Handwashing Station w/Sensored Water Faucet

Model #	Wgt	Description	Worksurface H"	W" x H" x D"
MCC4500-CJ-375426-AC	287	Stainless Sink w/Cold Water Only, Hygiene Station, Trash Bin	36	37 x 54 x 26
MCC4500-HJ-375426-AC	287	Stainless Sink w/Hot & Cold Water, Hygiene Station, Trash Bin	36	37 x 54 x 26

**Overall Depth: 27.125"**

# of **OPTIONAL** locks required: 1

Flow rate of .5 GPM, water tanks contain a 5 gallon fresh water tank and a 7 gallon waste water tank with drain hose for easy drain. HM & HJ units include a hot water heater.



MCC3500

### Handwashing Station w/Metered Water Faucet

Model #	Wgt	Description	Worksurface H"	W" x H" x D"
MCC4500-CM-375426-AC	287	Stainless Sink w/Cold Water Only, Hygiene Station, Trash Bin	36	37 x 54 x 26
MCC4500-HM-375426-AC	287	Stainless Sink w/Hot & Cold Water, Hygiene Station, Trash Bin	36	37 x 54 x 26

**Overall Depth: 27.125"**

# of **OPTIONAL** locks required: 1

### Sanitizing Station

Model #	Wgt	Description	Worksurface H"	W" x H" x D"
MCC3500-245426-AC	231	Hygiene Station, Trash Bin	36	24 x 54 x 26

**Overall Depth: 27.125"**